

Stock-pot stove G-2KB 1K700



- ▶ Two-circle burner
- ✓ Connected load: 7 kW
- ✓ Gas type: Liquid gas



- ▶ Pot diameter min.: 225 mm
- ▶ Load-bearing capacity: 70 kg

Description

Free-standing gas cooker with twin-ring burner, 7 kW, Pilot flame, Ignition guard. For pots from Ø 22.5 cm. Pressure regulator up to 50 mbar required. CNS 18/10 stainless steel, robust and durable. For catering and commercial kitchens requiring a stable, medium gas output for daily large-pot cooking.

Features

- | | |
|-------------------------------|--|
| • Gas type: | Liquid gas
Natural gas nozzles H and L are enclosed |
| • Gas burner: | Two-circle burner |
| • Ignition type: | Manual ignition |
| • Ignition guard: | Yes |
| • Pilot flame: | Yes |
| • Load-bearing capacity max.: | 70 kg |
| • Power: | 7 kW |
| • Operating mode: | Gas |
| • Properties: | - |
| • Number of hobs: | 1 |
| • Output hob(s) max.: | 7000 W |
| • Control unit: | Toggle |
| • Material: | CNS 18/10
Cast ribbed frame |
| • Important information: | The pot diameter must be at least 22.5 cm
A pressure reducer of max. 50 mbar is necessary |

▶ Continue on the next page



Stock-pot stove G-2KB 1K700

- Size: W 450 x D 475 x H 500 mm
- Weight: 20.2 kg



Stock-pot stove G-2KB 1K700

Add on Products

Gas connection set GW-AI



- Suitable for commercial use: Yes
- Can be used in: Inner and outer area
- Important information: -
- Size: W 64 x D 61 x H 27 mm
- Weight: 1.3 kg

Code-No. 500180
GTIN 4015613586557