

Water softening system WEH1350



► Output capacity at 10° dH: 1350 litres / day



► Digital display for setting:

- ✓ Water hardness
- ✓ Interval
- ✓ Regeneration
- ✓ Time
- ✓ Language

Description

System protection for dishwashers

Features

- Water intake temperature from: 5 °C
- Water intake temperature to: 40 °C
- Setting possibilities: Interval
- Regeneration
- Language
- Time
- Water hardness
- Flow rate or time period
- Regeneration: 1,5 - 6 bar
- Operating pressure: 20 kg
- Brine tank salt store: 0.7 kg / regeneration
- Salt consumption: 66 min.
- Regeneration time: Yes
- Digital display: 0.03 kW | 230 V | 50/60 Hz
- Power load: 3/4"
- Water connection: Grey
- Colour: 1 unit
- Connection capacity:

► Continue on the next page



Water softening system WEH1350


- Output capacity: 1,350 litres / day at 10° dH (total hardness)
- Designed for: Commercial dishwashers
- With active carbon: No
- Material: Plastic
- Important information: -
- Size: W 265 x D 430 x H 485 mm
- Weight: 8.84 kg



Water softening system WEH1350

Add on Products

Connection kit WEH1350/1500



- Water intake temperature: 40 °C
- Set comprises:
 - 1 hose 1/2" for regeneration, length 2 m
 - 1 hose 3/4" for water connection, length 1.5 m
- Material: Plastic (PVC)
- Important information: -
- Size: W 50 x D 2,000 x H 50 mm
- Weight: 0.55 kg

Code-No. 109884
GTIN 4015613630748