

## Water softening system WEH1500



- Capacity: 1,500 litres / at 10° dH (total hardness)



- Cost-effective and environmentally friendly thanks to reduction in required detergent quantity



- Reduction in limescale in the appliance and on the washed items through decrease in water hardness



- Acoustic signal if salt reservoir fill level is low

### Description

The water softening system reduces limescale in commercial dishwashers and optimises the results of washing due to fewer deposits of hardeners on the washed items. Thanks to the softer water, the amount of detergent needed is minimised. An acoustic signal indicates a low level in the salt reservoir.

### Features

- Water intake temperature from: 1 °C
- Water intake temperature to: 30 °C
- Setting possibilities: Interval  
Regeneration  
Time  
Water hardness  
Day of the week  
Flow rate or time period
- Regeneration: 2 - 6 bar
- Operating pressure: 20 kg
- Brine tank salt store: 0.7 kg / regeneration
- Salt consumption: 45 min.
- Regeneration time: Yes
- Digital display: 0.005 kW | 230 V | 50 Hz
- Power load: 3/4"
- Water connection: Grey
- Colour: 1 unit
- Connection capacity:

► Continue on the next page



## Water softening system WEH1500

- Output capacity: 1,500 litres / day at 10° dH (total hardness)
- Designed for: Commercial dishwashers
- With active carbon: Yes
- Material: Plastic
- Important information: -
- Size: W 260 x D 465 x H 478 mm
- Weight: 8.52 kg

