

Cooling top GL3-1501



- ▶ GN capacity:
 - ✓ 5 x 1/3 GN + 1 x 1/2 GN
 - ✓ Max. depth of GN containers: 150 mm
- ▶ GN containers not included in the delivery

Description

Clean and hygienic – a glass top for germ protection

Features

- | | |
|--------------------------------|------------------------------------|
| • Front pane: | Turned-down edges |
| • Power load: | 0,174 kW 230 V 50 Hz |
| • Material: | Chrome-nickel steel |
| | Glass |
| • Including: | 1 bar: length 326 mm, width 77 mm |
| | 6 bars: length 326 mm, width 25 mm |
| | 4 bars: length 181 mm, width 25 mm |
| | Yes |
| • Safety glass: | - |
| • Important information: | - |
| • Type of glass: | Single glazing |
| • Size glass superstructure: | W 1490 x D 390 x H 195 mm |
| • Temperature range: | 0 °C to 10 °C |
| • Control unit: | Electronic |
| | Knob |
| • Glass top unit design, back: | Open |
| • Control lamp: | ON/OFF |
| • Temperature control: | Digital |

▶ Continue on the next page

Cooling top GL3-1501

• Climate class:	N
• Cooling:	Static
• Coolant:	R290 / 0,030 kg
• Digital display:	Yes
• Lighting:	-
• Delivery state:	Building kit (simple assembly)
• Depth GN container max.:	150 mm
• Automatic defrosting function:	Yes
• Drip water evaporation:	Yes
• ON/OFF switch:	Yes
• Capacity GN:	5 x 1/3 GN + 1 x 1/2 GN
• Properties:	Cooling aggregate with cooling tray
• Design:	With glass top
• Not included in delivery:	GN containers
• Size:	W 1,500 x D 395 x H 460 mm
• Weight:	45.5 kg

