

Tilting frying pan G120LHK



- ▶ Pan made of CNS
- ✓ Contents: 120 litres
- ✓ Water intake fitting



- ▶ Temperature range: 100 °C to 300 °C
- ▶ Gas heating by tube burner made of CNS
- ▶ Pilot flame ignition
- ▶ Safety system with thermo element



- ▶ Manual tilt device

Description

Features

- | | |
|---------------------------|---|
| • Gas type: | Natural gas H
Liquid gas nozzles (50 mbar) are enclosed |
| • Pilot flame: | Yes |
| • Ignition type: | Piezo ignition |
| • Temperature range: | 100 °C to 300 °C |
| • Content: | 120 litre(s) |
| • Useful content: | 100 litre(s) |
| • Series: | - |
| • Water connection: | 12 mm |
| • Water supply tap: | Yes |
| • Material crucible: | Chrome-nickel steel |
| • Size crucible: | W 1090 x D 560 x H 225 mm |
| • Tilting device: | Manual |
| • Height-adjustable feet: | Yes |
| • Height adjustable: | 850 mm to 910 mm |
| • Properties: | Gas heater with stainless steel tube burner
Safety system with thermal element |

▶ Continue on the next page

Tilting frying pan G120LHK

- Operating mode: Gas
- Connected load gas: 30 kW
- Material: CNS 18/10
- Important information: -
- Size: W 1,200 x D 900 x H 900 mm
- Weight: 220 kg

