

Wall-mounted hood 700 w. motor, W1300



Description

Wall-mounted hood, 700 series, 1300 mm, with 184 W motor, up to 1,200 m³/h. Two CNS filters, grease collection channel, Type A flame arrestor, IP44. Commissioning with external controller. For kitchen lines with a width of 1300 mm requiring motorised extraction capacity with external control.

Features

• Number of fan motors/exhaust air outputs:	1
• Motor output:	184 W
• Fan regulation:	Via an external controller
• Cut-out for the motor:	232 x 208 mm
• Operating mode:	Exhaust air
• Material filter:	CNS 18/10
• Number of filters:	2
• Flame protection filter:	Type A
• With motor:	Yes
• Max. air throughput:	1200 m ³ /h
• Lighting:	yes
• Lamps (number + watt):	1 x 18 W
• Protection class:	IP44
• Including:	-
• Properties:	Blare-free light installed with grease protection cover Filter carrier with additional grease collection channel
• Assembly type:	Wall

► Continue on the next page

Wall-mounted hood 700 w. motor, W1300

- Available on request:
 - Ceiling hood
 - Other sizes
 - Wall hood series 1100
- Power load:
 - 0.202 kW | 230 V | 50-60 Hz
- Material:
 - CNS 18/10
- Important information:
 - Can only be commissioned with an additional controller
- Size:
 - W 1,300 x D 700 x H 450 mm
- Weight:
 - 35 kg



Wall-mounted hood 700 w. motor, W1300

Add on Products

Control, steplessly variable



- Designed for: Extractor hoods with 1 phase
- Output control: Manual
Stepless
- Assembly type: Wall
Extractor hood
- Protection class: IP54
- Control unit: Toggle

Code-No. 220110
GTIN 4015613603056