Bartscher
www.bartscher.com

Wall-mounted hood 700 w. motor, W1800

- Extractor bonnet with 3 filters
- Motor output: 184 watts

Description

Wall-mounted hood, Series 700, 1800 mm, with built-in Motor (184 W), up to 1,500 m³/h air flow rate and integrated Type A Flame protection filter. Three stainless steel filters with grease collection channel, glare-free Lighting. Note: Commissioning only with external controller. For commercial kitchens with high levels of steam.

Features

• Number of fan motors/exhaust air outputs:	1
• Motor output:	184 W
• Fan regulation:	Via an external controller
• Cut-out for the motor:	232 x 208 mm
• Operating mode:	Exhaust air
• Material filter:	CNS 18/10
• Number of filters:	3
• Flame protection filter:	Type A
• With motor:	Yes
• Max. air throughput:	1500 m³/h
• Lighting:	yes
• Lamps (number + watt):	1 x 18 W
• Protection class:	IP44
• Including:	-
• Properties:	Blare-free light installed with grease protection cover Filter carrier with additional grease collection channel
• Assembly type:	Wall

Continue on the next page

Subject to technical modifications and errors.

Code-No. 257180
GTIN 4015613600963

Wall-mounted hood 700 w. motor, W1800

• Available on request:	Ceiling hood Wall hood series 1100 Other sizes
• Power load:	0.202 kW | 230 V | 50-60 Hz
• Material:	CNS 18/10
• Important information:	Can only be commissioned with an additional controller
• Size:	W 1,800 x D 700 x H 450 mm
• Weight:	43 kg

Wall-mounted hood 700 w. motor, W1800

Add on Products

Control, steplessly variable

• Designed for:	Extractor hoods with 1 phase
• Output control:	Manual Stepless
• Assembly type:	Wall Extractor hood
• Protection class:	IP54
• Control unit:	Toggle

Code-No. 220110
GTIN 4015613603056

Subject to technical modifications and errors.