

Wall-mounted hood 700 w.motor, W2000



- ▶ Extractor bonnet with 4 filters
- ▶ Motor output: 184 watts



Description

Wall-mounted hood Series 700, 2000 mm, with 184 W motor, up to 1,600 m³/h. Four stainless steel filters, grease collection channel, Type A flame arrestor, IP44. Commissioning with external controller. For wide commercial kitchen lines with continuous and heavy steam generation at 2000 mm.

Features

- Number of fan motors/exhaust air outputs: 1
- Motor output: 184 W
- Fan regulation: Via an external controller
- Cut-out for the motor: 232 x 208 mm
- Operating mode: Exhaust air
- Material filter: CNS 18/10
- Number of filters: 4
- Flame protection filter: Type A
- With motor: Yes
- Max. air throughput: 1600 m³/h
- Lighting: yes
- Lamps (number + watt): 1 x 36 W
- Protection class: IP44
- Including: -
- Properties: Blare-free light installed with grease protection cover
Filter carrier with additional grease collection channel
- Assembly type: Wall

▶ Continue on the next page

Wall-mounted hood 700 w.motor, W2000

- Available on request:
 - Ceiling hood
 - Wall hood series 1100
 - Other sizes
- Power load:
 - 0.22 kW | 230 V | 50-60 Hz
- Material:
 - CNS 18/10
- Important information:
 - Can only be commissioned with an additional controller
- Size:
 - W 2,000 x D 700 x H 450 mm
- Weight:
 - 47 kg



Wall-mounted hood 700 w.motor, W2000

Add on Products

Control, steplessly variable



- Designed for: Extractor hoods with 1 phase
- Output control: Manual
Stepless
- Assembly type: Wall
Extractor hood
- Protection class: IP54
- Control unit: Toggle

Code-No. 220110
GTIN 4015613603056