Wall-mounted hood 700 w.motor, W2000

- Extractor bonnet with 4 filters
- Motor output: 184 watts

Description

Wall-mounted hood Series 700, 2000 mm, with 184 W motor, up to 1,600 m³/h. Four stainless steel filters, grease collection channel, Type A flame arrestor, IP44. Commissioning with external controller. For wide commercial kitchen lines with continuous and heavy steam generation at 2000 mm.

Features

• Number of fan motors/exhaust air outputs:	1
• Motor output:	184 W
• Fan regulation:	Via an external controller
• Cut-out for the motor:	232 x 208 mm
• Operating mode:	Exhaust air
• Material filter:	CNS 18/10
• Number of filters:	4
• Flame protection filter:	Type A
• With motor:	Yes
• Max. air throughput:	1600 m³/h
• Lighting:	yes
• Lamps (number + watt):	1 x 36 W
• Protection class:	IP44
• Including:	-
• Properties:	Blare-free light installed with grease protection cover Filter carrier with additional grease collection channel
• Assembly type:	Wall

Continue on the next page

Wall-mounted hood 700 w.motor, W2000

• Available on request:	Ceiling hood Wall hood series 1100 Other sizes
• Power load:	0.22 kW | 230 V | 50-60 Hz
• Material:	CNS 18/10
• Important information:	Can only be commissioned with an additional controller
• Size:	W 2,000 x D 700 x H 450 mm
• Weight:	47 kg

Wall-mounted hood 700 w.motor, W2000

Add on Products

Control, steplessly variable

• Designed for:	Extractor hoods with 1 phase
• Output control:	Manual Stepless
• Assembly type:	Wall Extractor hood
• Protection class:	IP54
• Control unit:	Toggle

Code-No. 220110
GTIN 4015613603056

Subject to technical modifications and errors.