


Wall-mounted hood 700, W1400



▶ Extractor bonnet with 2 filters



Description

Wall-mounted hood, Series 700, 1400 mm, without motor – two CNS filters with grease collection channel, Type A flame arrestor, 36 W lighting, IP44. For kitchens with an external extractor system looking for a compact, illuminated 1400 mm hood without its own motor.

Features

• Operating mode:	Exhaust air
• Material filter:	CNS 18/10
• Number of filters:	2
• Flame protection filter:	Type A
• With motor:	No
• Lighting:	yes
• Lamps (number + watt):	1 x 36 W
• Protection class:	IP44
• Including:	-
• Properties:	Blare-free light installed with grease protection cover Filter carrier with additional grease collection channel
• Assembly type:	Wall
• Available on request:	Ceiling hood Wall hood series 1100 Other sizes
• Power load:	0.036 kW 230 V 50-60 Hz
• Material:	CNS 18/10

▶ Continue on the next page

Wall-mounted hood 700, W1400

- Important information: -
- Size: W 1,400 x D 700 x H 450 mm
- Weight: 31 kg



Wall-mounted hood 700, W1400

Add on Products

Control, steplessly variable



- Designed for: Extractor hoods with 1 phase
- Output control: Manual
Stepless
- Assembly type: Wall
Extractor hood
- Protection class: IP54
- Control unit: Toggle

Code-No. 220110
GTIN 4015613603056