

Wall-mounted hood 900 w.motor, W2000



- ▶ Extractor bonnet with 4 filters
- ▶ Motor output: 184 watts



Description

Features

- | | |
|---|---|
| • Number of fan motors/exhaust air outputs: | 1 |
| • Motor output: | 184 W |
| • Fan regulation: | Via an external controller |
| • Cut-out for the motor: | 232 x 208 mm |
| • Operating mode: | Exhaust air |
| • Material filter: | CNS 18/10 |
| • Number of filters: | 4 |
| • Flame protection filter: | Type A |
| • With motor: | Yes |
| • Max. air throughput: | 1600 m ³ /h |
| • Lighting: | yes |
| • Lamps (number + watt): | 1 x 36 W |
| • Protection class: | IP44 |
| • Including: | - |
| • Properties: | Blare-free light installed with grease protection cover
Filter carrier with additional grease collection channel |
| • Assembly type: | Wall |

▶ Continue on the next page

Wall-mounted hood 900 w.motor, W2000

- Available on request:
 - Ceiling hood
 - Wall hood series 1100
 - Other sizes
- Power load:
 - 0.22 kW | 230 V | 50-60 Hz
- Material:
 - CNS 18/10
- Important information:
 - Can only be commissioned with an additional controller
- Size:
 - W 2,000 x D 900 x H 450 mm
- Weight:
 - 49 kg



Wall-mounted hood 900 w.motor, W2000

Add on Products

Control, steplessly variable



- Designed for: Extractor hoods with 1 phase
- Output control: Manual
Stepless
- Assembly type: Wall
Extractor hood
- Protection class: IP54
- Control unit: Toggle

Code-No. 220110
GTIN 4015613603056