

Vacuum packaging machine K 250/150L



Description

Powerful and solid chamber vacuum machine with intuitive control. Enclosed insert plates achieve height compensation in the chamber as required.

Features

• Material lid:	Plexiglas
• Chamber dimensions:	W 256 x D 370 x H 125 mm
• Colour:	Silver
• Functions:	Combined vacuuming and sealing
• Vacuum pump:	150 L / min. (8-9 m ³ / hours)
• Vacuum control:	-
• Vacuuming intensity can be regulated:	No
• Length welding rod:	250 mm
• Number of welded joints:	1
• Maximum vacuum:	-995 mbar
• Welding duration can be regulated:	6 levels
• Control unit:	Toggle
• Lighting:	No
• Digital display:	No
• ON/OFF switch:	Yes
• Control lamp:	Combined vacuuming and sealing ON/OFF

► Continue on the next page



► Functions: Combined vacuuming and sealing

► Vacuum pump: 150 L/min. (approx. 8/9 m³/h)

► Number of sealing seams: 1

✓ Sealing rod length: 250 mm



► Sealing duration can be regulated: 6 levels



► 2 insert plates

✓ For height compensation in the chamber

Vacuum packaging machine K 250/150L

- Properties:
 - 2 insert plates for height compensation (250 x 300 x 17 mm)
- Including:
 - 0.5 kW | 230 V | 50 Hz
- Power load:
 - Stainless steel
- Material:
 - Plastic
- Important information:
 -
- Size:
 - W 320 x D 540 x H 265 mm
- Weight:
 - 29 kg



Vacuum packaging machine K 250/150L

Add on Products

Vacuum sealer roll set 220



- Set comprises: 2 vacuum film rolls
- Width roll: 22 cm
- Length roll: 5 m
- Film thickness: 80 µM
- Sous-Vide suitable: Yes
- Important information: -
- Size: W 220 x D 40 x H 40 mm

Code-No. 300418
GTIN 4015613474946

Vacuum bags K1,2L



- Content: 1.2 litre(s)
- Order quantity unit: 1 pack (100 bags)
- Bag size: 160 x 250 mm
- Film thickness: 90 µM
- Designed for: Chamber vacuuming units
- Design: Smooth
- Sous-Vide suitable: Yes

Code-No. 300311
GTIN 4015613610320

Code-No.
GTIN