

Hot cupboard 700, W1400, SB



Description

Features

- | | |
|--|--|
| • Available on request: | Special production |
| • Height adjustable: | The list price corresponds to the next higher standard dimension |
| • Tilting: | 850 mm to 900 mm |
| • Material work surface: | 40 mm |
| • Load-bearing capacity worktop, max.: | Stainless steel |
| • Size work surface: | 210 kg |
| • Power load: | W 1400 x D 700 mm |
| • Height-adjustable feet: | 2 kW 230 V 50/60 Hz |
| • Temperature range: | Yes |
| • Control unit: | 20 °C to 80 °C |
| | Electronic |
| | Toggle |
| • Size inside: | W 1255 x D 620 x H 580 mm |
| • Control lamp: | yes |
| • Temperature control: | Stepless |
| • Delivery state: | Permanently mounted |

► Continue on the next page

Hot cupboard 700, W1400, SB

- Type of door: Sliding door(s)
Single-sided
- ON/OFF switch: Yes
- Number of doors: 2
- Number of intermediate shelves: 1
- Load-bearing capacity intermediate shelf, max.: 210 kg
- Design intermediate shelf: Full-surface
- Height-adjustable immediate shelves: No
- Design inside: 2-partitions
- Properties: 40 mm edges turned down
Feet in square tubing 40 x 40 mm
Scotch-Brite sanding
CNS 18/10
- Material: -
- Important information: -
- Size: W 1,400 x D 700 x H 850 mm
- Weight: 86.4 kg



Hot cupboard 700, W1400, SB

Add on Products

Swivel castors 4AW



- Swivel casters: 4 swivel casters, 2 with brake
- Diameter casters: 125 mm
- Load-bearing capacity max., each: 150 kg
- Material: Stainless steel
Rubber
- Important information: -

Code-No. 308242
GTIN 4015613600307