

Hot cupboard 700, W2000, SB



Description

Warming cabinet Series 700, 2000 mm worktop, 40 mm upstand, two sliding doors, 2 kW. Stepless control up to 80 °C. For wide serving areas that wish to combine maximum warming width with an upstand and 40 mm splash guard.

Features

• Available on request:	Special production
• Height adjustable:	The list price corresponds to the next higher standard dimension
• Tilting:	850 mm to 900 mm
• Material work surface:	40 mm
• Load-bearing capacity worktop, max.:	Stainless steel
• Size work surface:	210 kg
• Power load:	W 2000 x D 700 mm
• Height-adjustable feet:	2 kW 230 V 50/60 Hz
• Temperature range:	Yes
• Control unit:	20 °C to 80 °C
	Electronic
	Toggle
• Size inside:	W 1855 x D 620 x H 580 mm
• Control lamp:	yes
• Temperature control:	Stepless
• Delivery state:	Permanently mounted

► Continue on the next page

Hot cupboard 700, W2000, SB

- Type of door: Sliding door(s)
Single-sided
- ON/OFF switch: Yes
- Number of doors: 2
- Number of intermediate shelves: 1
- Load-bearing capacity intermediate shelf, max.: 178 kg
- Design intermediate shelf: Full-surface
- Height-adjustable intermediate shelves: No
- Design inside: 2-partitions
- Properties: 40 mm edges turned down
Feet in square tubing 40 x 40 mm
Scotch-Brite sanding
CNS 18/10
- Material: -
- Important information: -
- Size: W 2,000 x D 700 x H 850 mm
- Weight: 112.7 kg



Hot cupboard 700, W2000, SB

Add on Products

Swivel castors 4AW



- Swivel casters: 4 swivel casters, 2 with brake
- Diameter casters: 125 mm
- Load-bearing capacity max., each: 150 kg
- Material: Stainless steel
Rubber
- Important information: -

Code-No. 308242
GTIN 4015613600307